

## **Smartet Technology Development Co., Ltd**

Building 1, No.1 North YongXing Road,YongXing Industrial Park,HengLan Town, Zhong Shan City Guang DongChina Tel:0086-760-88873088 Fax:0086-760-88873008 web:www.smartet.net www.perfwipe.com

#### **Cleanroom Swab Data Sheet**

#### Nonwoven Cleanroom Swabs SSTX762

## **Description**

PERFWIPE Swab Series is made from the cleanest 100% polyester (hydroentangled) nowoven materials. The complete thermal bond construction eliminates adhesive contamination.

Cleanroom manufactured, made to exacting and consistent tolerances using high-precision automated processes. Packaged in a silicone-free and amide-free bag.

### **Features & Benefits**

- 1. Double layer of nonwoven polyester fabric for enhanced absorbency
- 2. Hydroentangled polyester for use on sensitive surfaces.
- 3. Excellent chemical resistance for compatibility with a variety of solutions
- 4. Cleanroom processed-providing ultra low levels of particles, NVR's (non volatile residuce) and ions.
- 5. 100% virgin polypropylene handle ensures no additional contaminants are introduced while offering excellent chemical resistance.
- 6. Autoclavable in dry heat and steam.

## Sampling

- 1. Nonwoven polyester head entraps contaminants in hydroentlangled structure during sampling. This allows maximum contaminant capture and release into the diluent to provide for excellent recovery rates.
- 2. This swab is most effective with solvents other than water.

## **Applications**

- 1. Cleaning sensitive surface such is optical assemblies
- 2. Solvent use (such as IPA)
- 3. Cleaning of grooves, tracks, slots and other small spaces.
- 4. Appropriate for use with temperatures less than 410°F

#### **Industries**

- 1. Biologics
- 2. Medical Device
- 3. Microelectronics
- 4. Optics
- 5. Pharmaceuticals
- 6. Semiconductor



# **Smartet Technology Development Co., Ltd**

Building 1, No.1 North YongXing Road,YongXing Industrial Park,HengLan Town, Zhong Shan City Guang DongChina
Tel:0086-760-88873088 Fax:0086-760-88873008 web:www.smartet.net www.perfwipe.com

Item No.: SSTX762

## **Physical Characteristics**

Head Material -- Hydroentangled Polyester

Head Width --6.8mm(0.268")

Head Thickness -- 2.6mm(0.102")

Head Length -- 16.8mm(0.661")

Handle Material -- Polypropylene

Handle Width -- 3.2mm (0.126")

Handle Thickness -- 3.2mm (0.126")

Total Swab Length -- 162.3mm (6.390")

Handle Length -- 145.5mm (5.728")

Head Bond -- Thermal

Handle Color -- Light Green

#### **Contamination Characteristics**

Particles, Readily releasable

Particles 0.5um<5000 counts/swab

Inos, ug/swab

Calcium --0.08

Chloride -- 0.06

Potassium -- 0.02

Sodium -- 0.06

### Nonvolatile Residue, mg/swab

DIW Extractant -- 0.01

IPA Extractant -- 0.01

## **Packaging**

100 swabs/bag,50 bags/case

